




Tel : (+852) 2712 2181 E-mail : sales@fengyuan.com.hk






WORKING DIAGRAM

- WORKING AREA WITH IN-SHAPE STABILIZATION
- MAXIMUM AREA







IVECO EUROCARGO

INFO

OUTRIGGERS



WORKING HEIGHT 38,50 m

HE+HE



BASKET HEIGHT **36,50 m**



MAX OUTREACH
30,00 m



BASKET LOAD CAPACITY
300 kg



BASKET SIZE **2200/3200x700x1100 mm**



BASKET ROTATION 180° + 180°



CONTROLS **Electric**




TURRET ROTATION 700°



GVW 18 ton

MIN. AREA MAX AREA MIN. AREA



STANDARD ACCESSORIES

O DATA SHEET

- SOCAGE convertible basket possibility (Eternit)
- $\cdot\,$ 2nd Jib 180 $^{\circ}$ manual rotation
- · Possibility of winch on removable JIB
- · Automatic stabilization
- · Partially stabilized working areas
- · Automatic closing
- Basket control station with console on Socage design including joystick and 7 "LCD display with real-time information
- Intercom with headphones for basket-ground communication
- Main and auxiliary motor start/stop control from the basket
- Multifunction radio remote control for emergency control of the aerial part from the ground and stabilization
- · 2 fixed roto-lamp on the vehicle cabin
- Socket 230V/400V
- · Heat exchanger on the hydraulic system
- · 2 folding sides, 2 fixed (h 150 mm)
- 4 outrigger plates
- Anti-corrosion treatment on unpainted components

SAFETY DATA

- · Emergency button
- Emergency manual hand pump
- · Automatic PTO deactivation
- · Cross-check of open stabilizers
- Anemometer
- · Load limiter in the basket
- Moment limiter with double safety and control of correct operation
- Multi axial device for visual control of frame stabilization
- Emergency descent with electric pump (in the absence of the auxiliary motor)
- Rotation brake of the turret with automatic insertion
 Hydraulic system with differentiated filtering with
- high efficiency filters both on the delivery lines and on the return lines
- Multifunction radio control for emergency control
- Automatism for rotation lock with extension of the stabilizers on one side only
- Chassis flatness sensor
- Flanged block valves